



# RoDAR: The first GNSS receiver-based anti-jam solution

Rod MacLeod



# Mission success depends on being able to operate in Delayed/Disconnected, Intermittent, & Limited Conditions.

NovAtel offers a variety of solutions that maximizes operations:

## OEM7 GNSS Receivers

*Multi-Constellation, Multi-Frequency, High Precision, High Dynamics.*

*Situational Awareness: analyse GNSS signals and interference*

## GPS Anti Jam Technology - GAJT

*Protects GPS L1 & L2 (inc. M-Code), Galileo E1, QZSS L1 & L2, & SBAS L1*

*Situational Awareness: jammer power and direction-finding*


## Robust Dual Antenna Receiver - RoDAR

*Single null on L1 and L5*

*Plus the features of an OEM7 receiver*

## SPAN Deeply Coupled GNSS-INS

*Deep Coupling gets the best out of both sensors*



*OEM7 GNSS Receivers*



*GPS Anti Jam Technology  
GAJT*



*Robust Dual Antenna Receiver  
RoDAR*




*SPAN Deeply Coupled GNSS + INS*

# Receiver based protection

## NovAtel's commercially available solutions for robust PNT



*RoDAR enabled OEM718D /OEM7720 based products*




*GNSS Resilience and Integrity Technology (GRIT) on all OEM7 Receivers*

### GRIT (GNSS Resilience and Integrity Technology)


- **GNSS Spoofing Detection**  
Spoofing alerts, even before receiver 'captured'
- **GNSS Interference Toolkit**  
View the spectrum; inspect / filter out interference
- **Time-Tagged Digitized Samples**  
For SIGINT and interference location

### RODAR (Robust Dual Antenna Receiver)


- Anti-jam on OEM7 Dual Antenna receivers
- Full Nulling algorithm in the firmware of the receiver
- Additional High Availability PNT positioning



*Spoofing Detection*



*Interference Toolkit*



*Time Tagged Samples*


# The GPS Jamming Threat




# The Jamming Threat



# RF interference can significantly degrade GNSS



# A 10 Watt jammer can deny GNSS for up to 50 km



# GAJT – Traditional GPS Anti-Jam Technology



# GAJT – GPS Anti-Jam Technology

## Controlled reception pattern antenna (CRPA) and electronics

- Replaces traditional antenna
- Uses space-frequency adaptive processing (SFAP) to protect against a wide range of jammers

## Protection

- GPS L1 & L2 (incl M-Code & SAASM), Galileo E1, QZSS L1 & L2, and SBAS L1
- GAJT-AE2 also protects GPS L5, Galileo E5a, SBAS L5 and NavIC L5
- Fixed latency choices (good timing performance)
- Simultaneously counter multiple jammers

## Situational Awareness

- Jammer power indication
- Jammer Direction-Finding

## In Service & Available Now

- Land, Sea and Air.
- Thousands operational worldwide
- Mature supply chain. Short lead-time. Reliable.
- Canadian Export License needed



**GAJT-410ML / GAJT-410MS**  
**4-element CRPA**



**GAJT-710ML / GAJT-710MS**  
**7-element CRPA**





**GAJT-AE-N/R & GAJT-AE2**  
**Separate 4-element CRPA**

# GPS Anti-Jam Technology (GAJT)


## How GAJT Works

GAJT defeats jammers by making nulls towards the interference, simultaneously on GPS L1, L2 or for AE2 on GPS L5

- 7 elements (GAJT-710ML/MS): up to 6 nulls
- 4 elements (GAJT-AE & GAJT-410): up to 3 nulls



4 elements:  
3 nulls



7 elements:  
6 nulls

## The Benefits of GAJT

**40 dB cancellation.** You can get 70 x closer to the jammer than before (“rule of thumb”).

**Situation Awareness.** Message shows that jamming is there – even if GAJT is defeating it.

**Direction Finding.** Points towards interference (separate display)






Example: GAJT-710ML as part of the Mounted Assured PNT (Positioning, Navigation and Timing) System (MAPS) Generation 1


Image courtesy of US Army




# 40dB of jamming mitigation can significantly improve range of operations



# A 10 Watt jammer can deny GNSS for up to 50 km



With 40 dB of protection we can navigate to within 100s of meters of the jammer





# RODAR: Receiver Based Spatial Processing



# Robust Dual Antenna Receiver (RoDAR)


- Anti-jam systems offer high levels of protection, but SWaP (Size, Weight & Power), system complexity and export controls limit use.
- There is a need for a low SWaP solution in commercial applications like small unmanned aerial vehicles (UAVs), last mile delivery robots and other autonomous machines.
- **RoDAR** – Receiver built-in anti-jamming protection
  - No military export controls from Canada or US. Commercial export controls only
  - Firmware upgradeable on some existing receivers
  - Requires antenna array
    - Two Antcom antennas mounted 8.5cm apart
    - Conformal antenna options available



# Dual-Antenna based Jammer Mitigation

All done in the NovAtel ASIC


- Operates as a dual input receiver in benign environments
- When jamming is detected:
  - RoDAR is automatically activated
  - Antenna 2 input used to dynamically null jamming present on Antenna 1
  - Resultant IF samples are jammer free and passed to the Tracking and PVT solution software
  - Increases power consumption by <4 Watts



RoDAR changes the gain pattern to attenuate interference

# Example: RoDAR protection vs Jammer Power - Chirp

- 1 Input jammer power increases until non-RoDAR solution is denied
- 2 Input jammer power continues to increase until RoDAR protected solution is denied
- 3 The RoDAR receiver provides approximately an additional 34 dB of jammer protection





# RoDAR - Key Features For Jamming Mitigation

- **Anti-Jamming Feature**
  - Dynamic protection against single L1 and L5 jammers
    - Null-Steering follows jammer
  - **OEM718D**
    - Protects L1 band simultaneously with L5 band.
    - Can use all MCMF in PNT solution
  - **OEM7720 / PwrPak7D**
    - Protects L5 (E5a sub-band) simultaneously with L5 (E5b sub-band)
    - Can use all MCMF in PNT solution
- **GNSS Interference & Resilience Technology (GRIT)**
  - Identify interference locations and types
  - Programmable filtering
  - Time-tagged digitized samples
- **Multi-Frequency Multi-Constellation (MCMF)**
  - Robustness by using GNSS signals across multiple constellations and bands
  - Independent signal acquisition for multiple constellations in each band
    - L1, L2 and L5 bands
    - GPS, GLONASS, Galileo, BeiDou, QZSS, SBAS constellations supported
- **Resilience by using High Availability Firmware**
  - Uses MCMF independent signal acquisition
  - Provides independent PVT on various frequencies and constellations

# UAV Example: Resilience by High-Capability OEM7 GNSS Receivers

High Availability Firmware (FW) hardens the reported position in a contested environment.



**Standard FW.** Gaps and position jumps (which might be rejected by autopilot)

**High Availability FW.** No gaps, position maintained throughout

# Robust Dual Antenna Receiver

## Summary

- Robust dual antenna receiver firmware can be installed on NovAtel's dual-antenna receiver cards
- Enables receiver-based anti-jam capability when using a 2-element CRPA or 2 independent antennas
- Smallest size, weight and power (SWaP) anti-jam solution possible
- >30 dB nominal protection
- Not ITAR/Canada Controlled Goods - subject to commercial export controls only



Receiver based AJ



2 element CRPA

# GNSS Resilience and Integrity Technology (GRIT)

- Interference detection & mitigation
- Spoofing detection
- Time tagged A/D samples

## GAJT

- Anti-jam antennas (4 and 7 elements)

## RoDAR

- Receiver based commercial anti-jam

**Thank you**

